lyondellbasell	These specifications/special requirement(s) are applicable specifically to LyondellBasell facilities for loading or unloading an ISO CONTAINER at a LyondellBasell site or a contracted 3PL location as applicable	
ISO CONTAINER SPECIFICATION		
PRODUCT  Material Characteristic and immed	ISOPROPYL ALCHOHOL	
material Onaracteristic and minice		See Product SDS
DOT SPECIFICATION	MUST BE APPROVED AND ALCHOHOL. DEDICATED OF SERVICES CONTAINER WE TRANSPORT OF ISOPROFILEGIBLE AND CORRECTL	K LITERS/LITRES, (STAINLESS STEEL ISO CONTAINER). CONTAINER D DESIGNATED BY LYONDELLBASELL, TO TRANSPORT ISOPROPYL CONTAINER IS PREFERRED BUT NOT REQUIRED, BUT DEDICATED VILL REQUIRE LYB WRITTEN PRE-APPOVAL PRIOR TO LOADING OR PYL ALCOHOL. SPECIAL NOTE: DATA PLATE INFORMATION MUST BE LY STAMPED. INSPECTION DOCUMENTATION MUST BE WITH DRIVER OF INSPECTION/TEST DATE VERIFICATION, TO HELP PREVENT
INSULATION	PREFERRED, BUT NOT RE	EQUIRED
HEATING CAPABILITIES	NOT REQUIRED	
GASKET MATERIAL		WHITE EPDM, VIRGIN TEFLON, TEFLON ROPE, TEFLON *DOME GASKET MUST GIVE A LEAK TIGHT SEAL UPON COMPLETION
CONNECTIONS/FITTINGS	(AS APPLICABLE). MUST E	STEEL, SOLID FLANGE OR PLUG MUST BE ATTACHED TO CONTAINER BE ABLE TO CAPABLE OF BEING SEALED WITH A 1/8" WIRE CABLE E COVER MUST CAPABLE OF BEING SEALED WITH 1/8" WIRE CABLE
LIQUID CONNECTION	RAIL OR VESSEL; BOTTOM ACCEPTABLE. DOMESTIC	ID FLANGE ON BOTTOM OUTLET IF CONTAINER IS TO BE LOAED ON M OUTLET MUST HAVE A SOLID CLOSURE; DUST CAPS NOT SHIPMENT: A FLANGED 3" MALE CAMLOCK (QUICK CONNECT) REAR LOADER . BOTH SHIPMENT TYPES MUST BE CAPABLE OF 8" WIRE CABLE SEAL.
VAPOR CONNECTION	AND VALVE MUST BE ABL	ITH BULL PLUG, BULL PLUG MUST BE ATTACHED WITH CHAIN/CABLE LE TO SEALED WI1/8" WIRE CABLE SEAL. NOTE: PROTECTIVE COVER R CONNECTION MUST ALSO HAVE THE CAPABILITY TO SEALED. THIS R DOMESTIC SHIPMENTS
NITROGEN PADDING	CONTAINER MUST HAVE	ORYING, MOISTURE, FLAMMABLE ATMOSPHERE CONTROL. CLEAN ISO A 5-7 PSIG PAD UPON ARRIVAL AT LOADING FACILITY. RE- R MAY RETURN WITH LAST OFF-LOADING PRESSURE OR MININUM OF
TANK CLEANLINESS	CERTIFICATE MUST BE AI CONTAINER MUST BE CLE THE PRIOR LYONDELLBA LAST CONTAINED WAS LY LYB PGUSP CONTAINER. REQUIRMENTS AS SHOW	ED, A CLEANING CERTIFICAE IS REQUIRED. SPECIAL NOTE: CLEANING N APPROVED FOOD GRADE/KOSHER CLEANING CERTIFICATE.  EAN, DRY, AND ODOR FREE. NOTE: IF ISO CONTAINER IS RE-LOAD, ASELL SHIPPING DOCUMENTS ARE REQUIRED AS PROOF THAT THE YB MATERIAL. THE CONTAINER MUST BE LISTED AS A DEDICATED CUSTOMER PICK-UP CONTAINER: MUST MEET THE SAME IN ABOVE IN ADDITION, MUST PROVIDE THE LAST 3 PRIOR ERIAL MUST BE APPROVED BY LYB TECH SERVICE REPRESENTATIVE
STRAPPING CHART REQUIRED	YES, NOTE: LEVEL GAUG	E/INDICATOR ALSO PREFERRED
HOSES		RED AT LYONDELLBASELL LOADING FACILITIES. <b>NOTE</b> : HOSE(S) ARE ARRIER FOR EXPORT SHIPMENTS.
ADDITIONAL APPURTENANCES OR REQUIREMENTS	ADDITIONAL EQUIPMENT, CONTAINER MUST BE CAI PRODUCT LABELING IS R FACILITY. DRIVER MUST E	SHOULD ALWAYS NOTE CARRIER'S INSTRUCTION FOR ANY , DRIVER'S REQUIREMENT, ETC. NOTE: ALL OPENING TO ISO PABLE OF BEING SEALED WITH 1/8" WIRE CABLE SEAL. NOTE: EQUIRED WITH CONTAINER/(DRIVER), UPON ARRIVAL TO LOADING ENSURE PRODUCT NAME/LABELING IS APPLIED TO BOTH SIDE OF TO LEAVING THE LOADING FACILITY.
OTHER	CARRIER MANIFEST DOC TIME. **DRIVER MUST ALV (PRIOR TO LOADING), DUI	IT AND MATCHING SAP SHIPPING NOTICE, TRANSWIDE CALL-OFF, OR UMENT. **DRIVER MUST ARRIVE AT PICKUP POINT AT SCHEDULED WAYS NOTIFY LYONDELL OF ANY REQUESTED LIGHT LOADING, E TO POTENTIAL EXCEEDING LEGAL GROSS WEIGHT. PLEASE ELL LOGISTICS WITH ANY QUESTIONS
PROHIBITED	PETS ARE PROHIBITED; A	ADDITIONAL PERSONNEL ONLY IF TEAM DRIVERS